



## Drill Bits

with 1/4" Hexagon Drive

### Punte elicoidale

con attacco esagonale 1/4"



## HSS-G

**M**

Nominal Diameter D	L 1	S 2	⬡	Art.-No.
1.0 mm	32	7	1/4"	67110
1.5 mm	32	10	1/4"	67115
2.0 mm	34	12	1/4"	67120
2.5 mm (M3)	36	14	1/4"	67125
3.0 mm	38	16	1/4"	67130
3.3 mm (M4)	40	18	1/4"	67133
3.5 mm	40	18	1/4"	67135
4.0 mm	44	20	1/4"	67140
4.2 mm (M5)	45	20	1/4"	67142
4.5 mm	46	24	1/4"	67145
5.0 mm (M6)	50	26	1/4"	67150
5.5 mm	50	26	1/4"	67155
6.0 mm	50	26	1/4"	67160
6.5 mm	50	30	1/4"	67165
6.8 mm (M8)	50	30	1/4"	67168
7.0 mm	50	30	1/4"	67170
7.5 mm	51	32	1/4"	67175
8.0 mm	51	32	1/4"	67180
8.5 mm (M10)	53	33	1/4"	67185
9.0 mm	53	33	1/4"	67190
9.5 mm	54	38	1/4"	67195
10.0 mm	54	38	1/4"	67198
10.2 mm (M12)	54	38	1/4"	67199

## Countersink Bits

90° - 3 Flutes

with 1/4" Hexagon Drive

### Frese per svasare

90° - 3 taglienti

con attacco esagonale 1/4"



## HSS

Nominal Diameter D	L 1	⬡	Art.-No.
6.3 mm	31	1/4"	67306
8.3 mm	31	1/4"	67308
10.4 mm	34	1/4"	67310
12.4 mm	35	1/4"	67312
16.5 mm	40	1/4"	67316
20.5 mm	41	1/4"	67320